

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** ACRYTECH - One component modified acrylic lacquer
 - **Article number:** TC-61230*****
 - **Product Code:** 001-26*****
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.
- **Application of the substance / the mixture** Paint / Coating
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
Nirlat, Tech-Coat site
Hayetsira st. 3, Rosh Haain 4801735
ISRAEL
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** During normal opening times: +972 8 9986330

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
 - **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.
 - **Hazard pictograms**



GHS02



GHS05



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
iso-butanol
n-butyl acetate

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 1)

ethyl acetate

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P303+P361+P353 **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 **Immediately call a POISON CENTER/doctor.**

P321 **Specific treatment (see on this label).**

P362+P364 **Take off contaminated clothing and wash it before reuse.**

P405 **Store locked up.**

P501 **Dispose of contents/container in accordance with local/regional/national/international regulations.**

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (isomer mix) ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-10%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1	iso-butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 2)

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Prevent seepage into sewage system, workpits and cellars.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Do not eat, drink or smoke while working. Refer to section 8 concerning personal precaution.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

TLV Short-term value: 6 mg/m³

141-78-6 ethyl acetate

TLV Short-term value: 6 mg/m³

108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin

TLV Short-term value: 6 mg/m³

78-83-1 iso-butanol

TLV Short-term value: 6 mg/m³

111-76-2 2-butoxyethanol

IOELV Short-term value: 246 mg/m³, 50 ppm
Long-term value: 98 mg/m³, 20 ppm
Skin

TLV Short-term value: 6 mg/m³

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Colour:	Various colours
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	77 °C

· **Flash point:** 27 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 315 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	11.5 Vol %

· **Vapour pressure at 20 °C:** 97 hPa

· **Density at 20 °C:** 0.9-1.3 g/cm³

· **Relative density** Not determined.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 5)

· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	100 s (ISO 6 mm)
· Solvent content:	
Organic solvents:	46.1 %
VOC (EC)	506,6 g/l
· Solids content:	52.8 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

EU

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 6)


SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|----------------------|
| · 14.1 UN-Number | UN1263 |
| · ADR, IMDG, IATA | UN1263 |
| · ADN | Void |
| · 14.2 UN proper shipping name | 1263 PAINT |
| · ADR | 1263 PAINT |
| · ADN | Void |
| · IMDG, IATA | PAINT |
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG | |
| · Class | Void |
| · IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 7)

· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · EMS Number: · Stowage Category	<i>Not applicable.</i> <i>F-E,S-E</i> B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L <i>Code: E1</i> <i>Maximum net quantity per inner packaging: 30 ml</i> <i>Maximum net quantity per outer packaging: 1000 ml</i>
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.*
- H226 Flammable liquid and vapour.*
- H302 Harmful if swallowed.*
- H304 May be fatal if swallowed and enters airways.*
- H312 Harmful in contact with skin.*
- H315 Causes skin irritation.*
- H318 Causes serious eye damage.*
- H319 Causes serious eye irritation.*
- H332 Harmful if inhaled.*
- H335 May cause respiratory irritation.*
- H336 May cause drowsiness or dizziness.*
- H373 May cause damage to organs through prolonged or repeated exposure.*

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.03.2018

Revision: 13.03.2018

Trade name: ACRYTECH - One component modified acrylic lacquer

(Contd. of page 8)

H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ori Raz orir@nirlat.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU